Numerical Solution of Differential Equations I

Endre Süli

Mathematical Institute University of Oxford 2020

Lecture 10

Motivation

Recall the system of differential equations from Lecture 9:



v varies rapidly near x = 0 while *u* is slowly varying for x > 0 and *v* is slowly varying for x > 1/45. Nevertheless, we are forced to use a step size of h < 2/45 in order to ensure that the method is absolutely stable.

Another motivating example: Van der Pol oscillator



Numerical solutions produced by Matlab's ode45 solver, for $\mu = 500$ and $\mu = 1000$.

◆□▶ ◆□▶ ◆臣▶ ◆臣▶ 三臣 - のへで

Adaptivity for stiff problems

$$y' = f(x, y), \qquad y(x_0) = y_0,$$
 (1)

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへぐ

for all $x \in [x_0, X_M]$, and make sure that this approximation is accurate up to a certain (absolute/relative) precision.

Adaptivity for stiff problems

$$y' = f(x, y), \qquad y(x_0) = y_0,$$
 (1)

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

for all $x \in [x_0, X_M]$, and make sure that this approximation is accurate up to a certain (absolute/relative) precision.

In addition, we would like to achieve such a precision in the fastest/cheapest way possible. How should this be done?

Adaptivity for stiff problems

$$y' = f(x, y), \qquad y(x_0) = y_0,$$
 (1)

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

for all $x \in [x_0, X_M]$, and make sure that this approximation is accurate up to a certain (absolute/relative) precision.

In addition, we would like to achieve such a precision in the fastest/cheapest way possible. How should this be done?

We shall describe two attempts, the first attempt being conceptually simpler, while the second attempt being the one preferred in practice for reasons which we shall explain.

A simple strategy could be to:

1. choose a one-step method of order p;

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三三 - のへぐ

A simple strategy could be to:

- 1. choose a one-step method of order *p*;
- 2. choose a natural number $N \in \mathbb{N}$ and compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using the step size $h = (X_M x_0)/N$;

A simple strategy could be to:

- 1. choose a one-step method of order *p*;
- 2. choose a natural number $N \in \mathbb{N}$ and compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using the step size $h = (X_M x_0)/N$;
- 3. choose a large natural number $\tilde{N} \in \mathbb{N}$ with $\tilde{N} > N$ and compute the approximate solution $\{\tilde{\mathbf{y}}_n\}_{n=0}^{\tilde{N}}$ using the step size $\tilde{h} = (X_M x_0)/\tilde{N}$.

A simple strategy could be to:

- 1. choose a one-step method of order *p*;
- 2. choose a natural number $N \in \mathbb{N}$ and compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using the step size $h = (X_M x_0)/N$;
- 3. choose a large natural number $\tilde{N} \in \mathbb{N}$ with $\tilde{N} > N$ and compute the approximate solution $\{\tilde{\mathbf{y}}_n\}_{n=0}^{\tilde{N}}$ using the step size $\tilde{h} = (X_M x_0)/\tilde{N}$.

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

This way, we obtain two approximations \mathbf{y}_N and $\tilde{\mathbf{y}}_{\tilde{N}}$ of $\mathbf{y}(X_M)$.

A simple strategy could be to:

- 1. choose a one-step method of order *p*;
- 2. choose a natural number $N \in \mathbb{N}$ and compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using the step size $h = (X_M x_0)/N$;
- 3. choose a large natural number $\tilde{N} \in \mathbb{N}$ with $\tilde{N} > N$ and compute the approximate solution $\{\tilde{\mathbf{y}}_n\}_{n=0}^{\tilde{N}}$ using the step size $\tilde{h} = (X_M x_0)/\tilde{N}$.

(日)((1))

This way, we obtain two approximations \mathbf{y}_N and $\tilde{\mathbf{y}}_{\tilde{N}}$ of $\mathbf{y}(X_M)$.

We may then use the (computable) difference $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_{N}\|$ to estimate the (noncomputable) error $\|\mathbf{y}(X_{M}) - \mathbf{y}_{N}\|$.

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三三 - のへぐ

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三三 - のへぐ

Else, we

1. increase N so that $N > \tilde{N}$;

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三 のへぐ

Else, we

- 1. increase N so that $N > \tilde{N}$;
- 2. compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using $h = (X_M x_0)/N$;

Else, we

- 1. increase N so that $N > \tilde{N}$;
- 2. compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using $h = (X_M x_0)/N;$
- 3. check whether $\|\mathbf{\tilde{y}}_{\tilde{N}} \mathbf{y}_{N}\| < \text{TOL}.$

Else, we

- 1. increase N so that $N > \tilde{N}$;
- 2. compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using $h = (X_M x_0)/N$;
- 3. check whether $\|\mathbf{\tilde{y}}_{\tilde{N}} \mathbf{y}_{N}\| < \text{TOL}.$

If $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\|$ is smaller than the target absolute tolerance TOL, then we finish the computation. Otherwise, we select a new \tilde{N} such that $\tilde{N} > N$, and compute $\{\tilde{\mathbf{y}}_n\}_{n=0}^{\tilde{N}}$ using $\tilde{h} = (X_M - x_0)/\tilde{N}$.

Else, we

- 1. increase N so that $N > \tilde{N}$;
- 2. compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using $h = (X_M x_0)/N$;
- 3. check whether $\|\mathbf{\tilde{y}}_{\tilde{N}} \mathbf{y}_{N}\| < \text{TOL}.$

If $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\|$ is smaller than the target absolute tolerance TOL, then we finish the computation. Otherwise, we select a new \tilde{N} such that $\tilde{N} > N$, and compute $\{\tilde{\mathbf{y}}_n\}_{n=0}^{\tilde{N}}$ using $\tilde{h} = (X_M - x_0)/\tilde{N}$.

This procedure is repeated (alternating N and \tilde{N}) until $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_{N}\|$ falls below the target absolute tolerance TOL.

Else, we

- 1. increase N so that $N > \tilde{N}$;
- 2. compute the approximate solution $\{\mathbf{y}_n\}_{n=0}^N$ using $h = (X_M x_0)/N$;
- 3. check whether $\|\mathbf{\tilde{y}}_{\tilde{N}} \mathbf{y}_{N}\| < \text{TOL}.$

If $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\|$ is smaller than the target absolute tolerance TOL, then we finish the computation. Otherwise, we select a new \tilde{N} such that $\tilde{N} > N$, and compute $\{\tilde{\mathbf{y}}_n\}_{n=0}^{\tilde{N}}$ using $\tilde{h} = (X_M - x_0)/\tilde{N}$.

This procedure is repeated (alternating N and \tilde{N}) until $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_{N}\|$ falls below the target absolute tolerance TOL.

The following argument suggests that the (computable) difference $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_{N}\|$ can be used to estimate the error $\|\mathbf{y}(X_{M}) - \mathbf{y}_{N}\|$.

The idea to use $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_{N}\|$ to estimate $\|\mathbf{y}(X_{M}) - \mathbf{y}_{N}\|$ is based on the following calculations.

$$\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}_{N}\|=\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}(X_{M})+\mathbf{y}(X_{M})-\mathbf{y}_{N}\|\leq C(\tilde{h}^{p}+h^{p})=(\alpha^{p}+1)Ch^{p}.$$

$$\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}_{N}\|=\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}(X_{M})+\mathbf{y}(X_{M})-\mathbf{y}_{N}\|\leq C(\tilde{h}^{p}+h^{p})=(\alpha^{p}+1)Ch^{p}.$$

Thus,

$$\begin{split} \|\mathbf{y}(X_M) - \mathbf{y}_N\| &= \|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}} + \tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\| \\ &\leq \|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}}\| + \|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\| \\ &\leq C\tilde{h}^p + (\alpha^p + 1)Ch^p \\ &\leq \alpha^p (Ch^p) + (\alpha^p + 1)(Ch^p). \end{split}$$

$$\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}_{N}\|=\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}(X_{M})+\mathbf{y}(X_{M})-\mathbf{y}_{N}\|\leq C(\tilde{h}^{p}+h^{p})=(\alpha^{p}+1)Ch^{p}.$$

Thus,

$$\begin{split} \|\mathbf{y}(X_M) - \mathbf{y}_N\| &= \|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}} + \tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\| \\ &\leq \|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}}\| + \|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\| \\ &\leq C\tilde{h}^p + (\alpha^p + 1)Ch^p \\ &\leq \alpha^p (Ch^p) + (\alpha^p + 1)(Ch^p). \end{split}$$

▲□▶ ▲□▶ ▲□▶ ▲□▶ ▲□ ● ● ●

For $\alpha < 1$, $\alpha^{p} \ll \alpha^{p} + 1$ (in relative terms).

$$\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}_{N}\|=\|\tilde{\mathbf{y}}_{\tilde{N}}-\mathbf{y}(X_{M})+\mathbf{y}(X_{M})-\mathbf{y}_{N}\|\leq C(\tilde{h}^{p}+h^{p})=(\alpha^{p}+1)Ch^{p}.$$

Thus,

$$\begin{split} \|\mathbf{y}(X_M) - \mathbf{y}_N\| &= \|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}} + \tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\| \\ &\leq \|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}}\| + \|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\| \\ &\leq C\tilde{h}^p + (\alpha^p + 1)Ch^p \\ &\leq \alpha^p (Ch^p) + (\alpha^p + 1)(Ch^p). \end{split}$$

For $\alpha < 1$, $\alpha^{p} \ll \alpha^{p} + 1$ (in relative terms).

Therefore, the term $\|\mathbf{y}(X_M) - \tilde{\mathbf{y}}_{\tilde{N}}\|$ has a minor contribution, and $\|\tilde{\mathbf{y}}_{\tilde{N}} - \mathbf{y}_N\|$ may be used to estimate $\|\mathbf{y}(X_M) - \mathbf{y}_N\|$.

This first adaptive strategy could deliver an accurate solution, but it is likely to be inefficient: whenever the target tolerance is not met we need to compute another solution from scratch on a finer mesh on the entire interval $[x_0, X_M]$.

Second attempt

To improve efficiency, we can try to control the consistency error for each mesh point x_n .

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三三 - のへぐ

Second attempt

To improve efficiency, we can try to control the consistency error for each mesh point x_n .

We have shown that (up to a constant factor, independent of h) the global error of a one-step method is bounded by the maximum of the consistency error.

▲□▶ ▲□▶ ▲□▶ ▲□▶ ▲□ ● ● ●

Second attempt

To improve efficiency, we can try to control the consistency error for each mesh point x_n .

We have shown that (up to a constant factor, independent of h) the global error of a one-step method is bounded by the maximum of the consistency error.

The hope is therefore that we may compute a sufficiently accurate numerical solution by adapting the step size locally, that is, by selecting a suitable h_n for every x_n to control the local size of the consistency error.

To estimate the consistency error at $x = x_n$, in addition to the one step method

$$\mathbf{y}_{n+1} = \mathbf{y}_n + h\mathbf{\Phi}(x_n, \mathbf{y}_n; h) =: \mathbf{\Psi}(x_n, \mathbf{y}_n; h), \qquad n = 0, 1, \dots;$$

of order p being used, we consider an additional one-step method

$$\tilde{\mathbf{y}}_{n+1} = \tilde{\mathbf{y}}_n + h\tilde{\mathbf{\Phi}}(x_n, \tilde{\mathbf{y}}_n; h) =: \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h), \qquad n = 0, 1, \dots,$$

of order \tilde{p} , with $\tilde{p} > p$, and we compute

$$\operatorname{ERR}(x_n; h) := \| \tilde{\boldsymbol{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \boldsymbol{\Psi}(x_n, \mathbf{y}_n; h) \|.$$
(2)

◆□▶ ◆□▶ ◆三▶ ◆三▶ 三三 のへぐ

To estimate the consistency error at $x = x_n$, in addition to the one step method

$$\mathbf{y}_{n+1} = \mathbf{y}_n + h\mathbf{\Phi}(x_n, \mathbf{y}_n; h) =: \mathbf{\Psi}(x_n, \mathbf{y}_n; h), \qquad n = 0, 1, \dots;$$

of order p being used, we consider an additional one-step method

$$\tilde{\mathbf{y}}_{n+1} = \tilde{\mathbf{y}}_n + h\tilde{\mathbf{\Phi}}(x_n, \tilde{\mathbf{y}}_n; h) =: \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h), \qquad n = 0, 1, \dots,$$

of order \tilde{p} , with $\tilde{p} > p$, and we compute

$$\operatorname{ERR}(x_n; h) := \|\tilde{\boldsymbol{\Psi}}(x_n, \tilde{\boldsymbol{y}}_n; h) - \boldsymbol{\Psi}(x_n, \boldsymbol{y}_n; h)\|.$$
(2)

The idea behind using (2) to estimate the consistency error T_n is that, if the error has been controlled from x_0 up until x_n , for some $n \ge 1$, then the difference between $\mathbf{y}(x_n)$ and \mathbf{y}_n is "negligible", and therefore \mathbf{y}_n can be assumed to be equal to $\tilde{\mathbf{y}}_n$.

Hence,

$$hT_n = \mathbf{y}(x_{n+1}) - \mathbf{\Psi}(x_n, \mathbf{y}(x_n); h)$$

= $\mathbf{y}(x_{n+1}) - \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) + \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) - \mathbf{\Psi}(x_n, \mathbf{y}(x_n); h)$
 $\approx \mathbf{y}(x_{n+1}) - \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) + \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \mathbf{\Psi}(x_n, \mathbf{y}_n; h)$
 $\approx Ch^{\tilde{p}+1} + \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \mathbf{\Psi}(x_n, \mathbf{y}_n; h).$

Hence,

$$hT_n = \mathbf{y}(x_{n+1}) - \mathbf{\Psi}(x_n, \mathbf{y}(x_n); h)$$

= $\mathbf{y}(x_{n+1}) - \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) + \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) - \mathbf{\Psi}(x_n, \mathbf{y}(x_n); h)$
 $\approx \mathbf{y}(x_{n+1}) - \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) + \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \mathbf{\Psi}(x_n, \mathbf{y}_n; h)$
 $\approx Ch^{\tilde{p}+1} + \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \mathbf{\Psi}(x_n, \mathbf{y}_n; h).$

Since the left-hand side is of the order $\mathcal{O}(h \times h^p) = \mathcal{O}(h^{p+1})$ and $\tilde{p} > p$, it follows that the term $\approx Ch^{\tilde{p}+1}$ on the right-hand side is "negligible" compared to the "leading-order term"

$$\tilde{\Psi}(x_n, \tilde{\mathbf{y}}_n; h) - \Psi(x_n, \mathbf{y}_n; h).$$

▲□▶ ▲□▶ ▲□▶ ▲□▶ ▲□ ● ● ●

Hence,

$$hT_n = \mathbf{y}(x_{n+1}) - \mathbf{\Psi}(x_n, \mathbf{y}(x_n); h)$$

= $\mathbf{y}(x_{n+1}) - \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) + \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) - \mathbf{\Psi}(x_n, \mathbf{y}(x_n); h)$
 $\approx \mathbf{y}(x_{n+1}) - \tilde{\mathbf{\Psi}}(x_n, \mathbf{y}(x_n); h) + \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \mathbf{\Psi}(x_n, \mathbf{y}_n; h)$
 $\approx Ch^{\tilde{p}+1} + \tilde{\mathbf{\Psi}}(x_n, \tilde{\mathbf{y}}_n; h) - \mathbf{\Psi}(x_n, \mathbf{y}_n; h).$

Since the left-hand side is of the order $\mathcal{O}(h \times h^p) = \mathcal{O}(h^{p+1})$ and $\tilde{p} > p$, it follows that the term $\approx Ch^{\tilde{p}+1}$ on the right-hand side is "negligible" compared to the "leading-order term"

$$\tilde{\Psi}(x_n, \tilde{\mathbf{y}}_n; h) - \Psi(x_n, \mathbf{y}_n; h).$$

Hence,

$$hT_n \approx \tilde{\Psi}(x_n, \tilde{\mathbf{y}}_n; h) - \Psi(x_n, \mathbf{y}_n; h).$$

▲□▶ ▲□▶ ▲□▶ ▲□▶ ▲□ ● ● ●

(ロ)、(型)、(E)、(E)、(E)、(O)へ(C)

at every step x_n

1. select an initial local step size h_n ;

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三三 - のへぐ

at every step x_n

- 1. select an initial local step size h_n ;
- 2. compute $ERR(x_n; h_n)$;

at every step x_n

- 1. select an initial local step size h_n ;
- 2. compute $ERR(x_n; h_n)$;
- 3. if this is smaller than a target tolerance TOL, we set $\mathbf{y}_{n+1} = \mathbf{\Psi}(x_n, \mathbf{y}_n; h_n)$; else, we choose a smaller h_n and return to step 2.

at every step x_n

- 1. select an initial local step size h_n ;
- 2. compute $ERR(x_n; h_n);$
- 3. if this is smaller than a target tolerance TOL, we set $\mathbf{y}_{n+1} = \mathbf{\Psi}(x_n, \mathbf{y}_n; h_n)$; else, we choose a smaller h_n and return to step 2.

To make this algorithm more efficient, it is common to increase the step h_n every time this step has been accepted, that is, to select βh_n for a suitable $\beta > 1$.

Remark Let TOL be a target absolute error tolerance and let $ERR(x_n; h_n) < TOL.$

Let TOL be a target absolute error tolerance and let $ERR(x_n; h_n) < TOL$. Then, the "optimal" β is

$$\beta = \beta_n = \sqrt[(p+1)]{\text{TOL}/\text{ERR}(x_n; h_n)}.$$
(3)

Let TOL be a target absolute error tolerance and let $ERR(x_n; h_n) < TOL$. Then, the "optimal" β is

$$\beta = \beta_n = \sqrt[(p+1)]{\text{TOL}/\text{ERR}(x_n; h_n)}.$$
(3)

Indeed, if $ERR(x_n; h_n) < TOL$, we could have chosen a larger h_n and still satisfied the tolerance criterion.

Let TOL be a target absolute error tolerance and let $ERR(x_n; h_n) < TOL$. Then, the "optimal" β is

$$\beta = \beta_n = \sqrt[(p+1)]{\text{TOL}/\text{ERR}(x_n; h_n)}.$$
(3)

Indeed, if $ERR(x_n; h_n) < TOL$, we could have chosen a larger h_n and still satisfied the tolerance criterion.

Let β_n be such that $\text{ERR}(x_n, \beta_n h_n) = \text{TOL}$, so that $\beta_n h_n$ is the ideal step size.

Let TOL be a target absolute error tolerance and let $ERR(x_n; h_n) < TOL$. Then, the "optimal" β is

$$\beta = \beta_n = \sqrt[(p+1)]{\text{TOL}/\text{ERR}(x_n; h_n)}.$$
(3)

・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・
 ・

Indeed, if $ERR(x_n; h_n) < TOL$, we could have chosen a larger h_n and still satisfied the tolerance criterion.

Let β_n be such that $\text{ERR}(x_n, \beta_n h_n) = \text{TOL}$, so that $\beta_n h_n$ is the ideal step size. Then, we deduce (3), because

 $\operatorname{ERR}(x_n;\beta_nh_n)\approx C(\beta_nh_n)^{p+1}=\beta_n^{p+1}Ch_n^{p+1}\approx\beta_n^{p+1}\operatorname{ERR}(x_n;h_n).$

To further improve the efficiency of this adaptive algorithm, it is convenient to use embedded Runge–Kutta methods, which limit the number of function evaluations.

▲□▶ ▲□▶ ▲ 三▶ ▲ 三▶ 三三 - のへぐ

To further improve the efficiency of this adaptive algorithm, it is convenient to use embedded Runge–Kutta methods, which limit the number of function evaluations.

Definition

Two Runge-Kutta methods are *embedded* if they use the same stages. The Butcher tableau of two embedded Runge-Kutta methods can be written as

are the Butcher tableaux of the two Runge–Kutta methods, respectively.

Example

The Heun¹–Euler method has the Butcher tableau:

are the Butcher tableaux of Heun's method

$$y_{n+1} = y_n + \frac{h}{2}[f(x_n, y_n) + f(x_n + h, y_n + hf(x_n, y_n))]$$

and the explicit Euler method $y_{n+1} = y_n + hf(x_n, y_n)$, respectively.

Example

MATLAB integrators for ODEs (such as the functions ode45, ode23, etc.) are based on embedded Runge–Kutta methods.²

 ¹Karl Heun (3 April 1859, Wiesbaden – 10 January 1929, Karlsruhe)
 ²See L. F. Shampine and M. W. Reichelt, *The MATLAB ODE suite* (1997).