

## Problem Sheet 2

1. In plane strain, show that a smooth single-valued displacement can exist only if the strain components  $e_{xx}$ ,  $e_{xy}$  and  $e_{yy}$  satisfy the *compatibility condition*

$$\frac{\partial^2 e_{yy}}{\partial x^2} - 2 \frac{\partial^2 e_{xy}}{\partial x \partial y} + \frac{\partial^2 e_{xx}}{\partial y^2} = 0.$$

Reformulate this relation in terms of the stress components  $\tau_{xx}$ ,  $\tau_{xy}$  and  $\tau_{yy}$ .

How many compatibility conditions do you think there are in three dimensions?

2. In the absence of a body force, the steady Navier equation takes the form

$$\frac{1}{r} \frac{\partial}{\partial r} (r \tau_{rr}) + \frac{1}{r} \frac{\partial \tau_{r\theta}}{\partial \theta} - \frac{\tau_{\theta\theta}}{r} = 0, \quad \frac{1}{r} \frac{\partial}{\partial r} (r \tau_{r\theta}) + \frac{1}{r} \frac{\partial \tau_{\theta\theta}}{\partial \theta} + \frac{\tau_{r\theta}}{r} = 0,$$

in plane polar coordinates. Show that these are satisfied identically by introducing an Airy stress function  $\mathfrak{A}$  such that

$$\tau_{rr} = \frac{1}{r^2} \frac{\partial^2 \mathfrak{A}}{\partial \theta^2} + \frac{1}{r} \frac{\partial \mathfrak{A}}{\partial r}, \quad \tau_{r\theta} = - \frac{\partial}{\partial r} \left( \frac{1}{r} \frac{\partial \mathfrak{A}}{\partial \theta} \right), \quad \tau_{\theta\theta} = \frac{\partial^2 \mathfrak{A}}{\partial r^2}.$$

[These may alternatively be obtained by transforming the Cartesian relationships using the chain rule.]

3. In plane strain, the two-dimensional stress tensor takes the form

$$\mathcal{T} = \begin{pmatrix} \tau_1 & 0 \\ 0 & \tau_2 \end{pmatrix}$$

with respect to *principal axes*, where  $\tau_1$  and  $\tau_2$  are the *principal stresses*. Show that, if the axes are rotated through an angle  $\theta$ , then  $\mathcal{T}$  is transformed to

$$\mathcal{T}' = \begin{pmatrix} \tau_1 \cos^2 \theta + \tau_2 \sin^2 \theta & (\tau_2 - \tau_1) \sin \theta \cos \theta \\ (\tau_2 - \tau_1) \sin \theta \cos \theta & \tau_1 \sin^2 \theta + \tau_2 \cos^2 \theta \end{pmatrix}.$$

Deduce that the maximum shear stress is  $S = |\tau_1 - \tau_2|/2$ .

Show that, with respect to arbitrary axes,  $S$  is given by

$$S^2 = \frac{(\tau_{xx} - \tau_{yy})^2}{4} + \tau_{xy}^2.$$

[The Tresca yield criterion states that a solid material will fail if  $S$  exceeds some critical yield stress  $\tau_Y$ .]

4. A gun barrel occupies the region  $a < r < b$  in plane polar coordinates. A uniform pressure  $P$  is applied to the inner surface  $r = a$  while the outer surface  $r = b$  is traction-free. Assume that the displacement is purely radial, so that  $\mathbf{u} = u_r(r)\mathbf{e}_r$ . By solving the Navier equation in polar coordinates, obtain the solution

$$u_r(r) = \frac{Pa^2}{2(b^2 - a^2)} \left( \frac{r}{\lambda + \mu} + \frac{b^2}{\mu r} \right),$$

and hence show that the maximum shear stress defined in Question 3 is given by

$$S = \frac{\tau_{\theta\theta} - \tau_{rr}}{2} = \frac{Pa^2b^2}{(b^2 - a^2)r^2}.$$

Deduce that the barrel will explode if

$$P > \tau_Y \left( 1 - \frac{a^2}{b^2} \right),$$

where  $\tau_Y$  is the Tresca yield stress.

5. Seek harmonic wave solutions  $\mathbf{u} = \mathbf{a}e^{i(\mathbf{k}\cdot\mathbf{x} - \omega t)}$  (real part assumed) of the dynamic Navier equation.

Show that there exists a unique scalar  $A$  and vector  $\mathbf{B}$  such that  $\mathbf{a} = A\mathbf{k} + \mathbf{B} \times \mathbf{k}$  and  $\mathbf{k} \cdot \mathbf{B} = 0$ .

Deduce that either  $\mathbf{B} = \mathbf{0}$ ,  $\rho\omega^2 = (\lambda + 2\mu)|\mathbf{k}|^2$  or  $A = 0$ ,  $\rho\omega^2 = \mu|\mathbf{k}|^2$ .

Show that the wave-speeds  $c_p = \sqrt{(\lambda + 2\mu)/\rho}$  and  $c_s = \sqrt{\mu/\rho}$  satisfy  $c_p > c_s$ .

6. An elastic medium occupies the half-space  $y < 0$  and the surface  $y = 0$  is stress-free. If the displacement is two-dimensional, with  $\mathbf{u} = (u(x, y, t), v(x, y, t), 0)^T$ , obtain the boundary conditions

$$(c_p^2 - 2c_s^2) \frac{\partial u}{\partial x} + c_p^2 \frac{\partial v}{\partial y} = \frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} = 0 \quad \text{on } y = 0.$$

Show that a *Rayleigh wave* can propagate close to the surface, with

$$\mathbf{u} = (\mathbf{u}_p e^{\kappa_p y} + \mathbf{u}_s e^{\kappa_s y}) \exp\{i(kx - \omega t)\},$$

where  $\kappa_p^2 = k^2 - \omega^2/c_p^2$  and  $\kappa_s^2 = k^2 - \omega^2/c_s^2$ . What restriction on the propagation speed  $c = \omega/k$  will ensure that  $\kappa_p$  and  $\kappa_s$  are both real (and positive)?

Deduce that the propagation  $c$  satisfies the equation

$$\left( 2 - \frac{c^2}{c_s^2} \right)^2 = 4 \left( 1 - \frac{c^2}{c_p^2} \right)^{1/2} \left( 1 - \frac{c^2}{c_s^2} \right)^{1/2},$$

and confirm graphically that this has only one real root in the range  $0 < c < c_s$ .

7. A uniform beam of line density  $\rho$  and length  $L$  lying along the  $x$ -axis under a tension  $T$  undergoes a small transverse displacement  $w(x, t)\mathbf{k}$ . Derive the governing equations

$$\frac{\partial T}{\partial x} = 0, \quad T \frac{\partial^2 w}{\partial x^2} + \frac{\partial^2 M}{\partial x^2} - \rho g = \rho \frac{\partial^2 w}{\partial t^2},$$

where  $M$  is the clockwise bending moment exerted on each cross-section of the beam and the gravitational acceleration is  $\mathbf{g} = -g\mathbf{k}$ .

Use an exact solution of the steady Navier equation to justify the constitutive relation

$$M = -EI \frac{\partial^2 w}{\partial x^2},$$

where  $E$  is Young's modulus and  $I$  is the moment of inertia of the cross-section about the  $y$ -axis.

If gravity is negligible and no transverse force is applied at the ends, which are clamped horizontally, justify the boundary conditions  $\partial w / \partial x = \partial^3 w / \partial x^3 = 0$  at  $x = 0$  and  $x = L$ . Show that the natural frequencies  $\omega$  of the beam are given by

$$\omega^2 = \frac{n^2 \pi^2}{\rho L^2} \left( \frac{n^2 \pi^2 EI}{L^2} + T \right),$$

and deduce that the beam is unstable if  $T < -\pi^2 EI / L^2$ .